

8. References

- [1] H. Tao, J. L. Duarte, and M.A.M. Hendrix 2008, “Three-port triple-half-bridge bidirectional converter with zero-voltage switching,” *IEEE Trans. Power Electron.*, vol. 23, no. 2, pp.782–792.
<http://dx.doi.org/10.1109/TPEL.2007.915023>
- [2] J. L. Duarte, M. Hendrix, and M. G. Simoes 2007, “Three-port bidirectional converter for hybrid fuel cell systems,”*IEEE Trans. Power Electron.*, vol. 22, no. 2, pp. 480–487.
<http://dx.doi.org/10.1109/TPEL.2006.889928>
- [3] H. Krishnaswami and N. Mohan 2009, “Three-port series-resonant DC–DC converter to interface renewable energy sources with bidirectional load and energy storage ports,”*IEEE Trans. Power Electron.*, vol. 24, no. 9–10, pp. 2289–2297.
- [4] H. Tao, A. Kotsopoulos, J. L. Duarte, and M. A. M. Hendrix 2008, “Family of multiport bidirectionalDC-DC converters,” in *Proc. IEEE Power Electron. Spec. Conf.*, pp. 796– 801.
- [5] Y. M. Chen, Y. C. Liu, and F. Y. Wu 2002, “Multi-input DC/DC converter based on the multiwinding transformer for renewable energy applications,” *IEEE Trans. Ind. Appl.*, vol.38, no. 4, pp. 1096–1104.
<http://dx.doi.org/10.1109/TIA.2002.800776>
- [6] Zhijun Qian, Osama Abdel-Rahman, and Issa atarseh 2010, “An Integrated Four-Port DC/DC Converter for Renewable Energy Applications” *IEEE Trans. Power Electronics*, Vol. 25, no. 7.
- [7] B. G. Dobbs and P. L. Chapman 2003, “A multiple-input DC-DC converter topology,” in *Proc. IEEE Power Electron. Lett.*,vol. 1, pp. 6– 9.
<http://dx.doi.org/10.1109/LPEL.2003.813481>
- [8] H. Tao, A. Kotsopoulos, J. L. Duarte, and M. A. M. Hendrix 2005, “Multi input bidirectional DC-DC converter combining DC-link and magnetic coupling for fuel cell systems,” in *Proc. IEEE Ind. Appl. Conf.*,pp. 2021–2028.
<http://dx.doi.org/10.1109/IAS.2005.1518725>